SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

MSX12446

Revision Date 06/20/2017

Version 1.2

SECTION 1.Identification

Product identifier

Product number	SX1244
Product name	Sulfuric Acid GR ACS
CAS-No.	7664-93-9

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Reagent for analysis

Details of the supplier of the safety data sheet

Company	EMD Millipore Corporation | 290 Concord Road, Billerica, MA 01821, United States of America | General Inquiries: +1-978-715-4321 | Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5) MilliporeSigma is a business of Merck KGaA, Darmstadt, Germany.
Emergency telephone	800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

SECTION 2. Hazards identification

GHS Classification

Corrosive to Metals, Category 1, H290
Skin corrosion, Category 1A, H314
Serious eye damage, Category 1, H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms

Signal Word
Danger

Hazard Statements
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary Statements

RECEIVED
JUN 20 2024
Safety

P234 Keep only in original container.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see supplemental first aid instructions on this label).
P363 Wash contaminated clothing before reuse.
P390 Absorb spillage to prevent material damage.
P405 Store locked up.
P406 Store in corrosive resistant stainless steel container with a resistant inner liner.
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. Composition/information on ingredients

Formula	H_2SO_4	H_2O_4S (Hill)
Molar mass	98.08 g/mol	

Hazardous ingredients

Chemical name (Concentration)
CAS-No.
sulphuric acid (>= 90 % - <= 100 %)
7664-93-9

Exact percentages are being withheld as a trade secret.

SECTION 4. First aid measures

Description of first-aid measures

General advice
First aider needs to protect himself.

First aider needs to protect himself.

Inhalation
After inhalation: fresh air. Call in physician.

After inhalation: fresh air. Call in physician.

Skin contact
In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

Eye contact
After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

Ingestion
After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation!). Call a physician immediately. Do not attempt to neutralize.

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation!). Call a physician immediately. Do not attempt to neutralize.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed
Irritation and corrosion, Cough, Shortness of breath, Nausea, Vomiting, Diarrhea, pain, Risk of blindness!
Irritation and corrosion, Cough, Shortness of breath
Risk of blindness!

Indication of any immediate medical attention and special treatment needed
No information available.

SECTION 5. Fire-fighting measures

Extinguishing media
Suitable extinguishing media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media
For this substance/mixture no limitations of extinguishing agents are given.
For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture
Not combustible.
Ambient fire may liberate hazardous vapors.
Fire may cause evolution of:
Sulfur oxides
Ambient fire may liberate hazardous vapors.

Advice for firefighters
Special protective equipment for fire-fighters
Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information
Cool closed containers exposed to fire with water spray. Prevent fire extinguishing water from contaminating surface water or the ground water system. Suppress (knock down) gases/vapors/mists with a water spray jet.

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

Environmental precautions

Do not let product enter drains.
Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.
Observe possible material restrictions (see sections 7 and 10).
Take up with liquid-absorbent and neutralizing material (e.g. Chemizorb® H^+, Art. No. 101595).
Dispose of properly. Clean up affected area.
Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10).
Take up with liquid-absorbent and neutralizing material (e.g. Chemizorb® H^+, Art. No. 101595).
Dispose of properly. Clean up affected area.

SECTION 7. Handling and storage

Precautions for safe handling

Observe label precautions.

Observe label precautions.

Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers
No metal containers.

Tightly closed.

Dry.

Tightly closed.

Store at room temperature.

SECTION 8. Exposure controls/personal protection

Exposure limit(s)

Ingredients

Basis	Value	Threshold limits	Remarks
sulphuric acid 7664-93-9			
ACGIH	Time Weighted Average (TWA):	0.2 mg/m³	Form of exposure: Thoracic fraction.
NIOSH/GUIDE	Recommended exposure limit (REL):	1 mg/m³	
OSHA_TRANS	PEL:	1 mg/m³	
Z1A	Time Weighted Average (TWA):	1 mg/m³	

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

Hygiene measures

Change contaminated clothing and immerse in water. Preventive skin protection Wash hands and face after working with substance.

Change contaminated clothing and immerse in water. Preventive skin protection Wash hands and face after working with substance.

Eye/face protection

Tightly fitting safety goggles

Tightly fitting safety goggles

Hand protection

full contact:

Glove material:	Viton (R)
Glove thickness:	0.7 mm
Break through time:	> 480 min

splash contact:

Glove material:	butyl-rubber
Glove thickness:	0.7 mm
Break through time:	> 120 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 890 Vitoject® (full contact), KCL 898 Butoject® (splash contact).
The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet and supplied by us as well as to the purpose specified by us. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment:
Acid-resistant protective clothing.

Acid-resistant protective clothing.

Respiratory protection
required when vapors/aerosols are generated.
Recommended Filter type: Filter P 2 (acc. to DIN 3181) for solid and liquid particles of harmful substances
The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are performed according to the instructions of the producer. These measures have to be properly documented.

required when vapors/aerosols are generated.

SECTION 9. Physical and chemical properties

Physical state	liquid
Color	colorless
Odor	odorless
Odor Threshold	Not applicable
pH	0.3 at 49 g/l 77 °F (25 °C)
Melting point	-4 °F (-20 °C)
Boiling point/boiling range	ca. 635 °F (335 °C) at 1,013 hPa
Flash point	Not applicable
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapor pressure	ca.0.0001 hPa at 68 °F (20 °C)

Relative vapor density	ca.3.4
Density	1.84 g/cm3 at 68 °F (20 °C)
Relative density	No information available.
Water solubility	at 68 °F (20 °C) soluble, (caution ! development of heat)
Partition coefficient: n-octanol/water	No information available.
Autoignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	ca.24 mPa.s at 68 °F (20 °C)
Explosive properties	Not classified as explosive.
Oxidizing properties	Oxidizing potential
Ignition temperature	Not applicable
Bulk density	Not applicable
Corrosion	May be corrosive to metals.

SECTION 10. Stability and reactivity

Reactivity

has a corrosive effect
strong oxidizing agent

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .
The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

A risk of explosion and/or of toxic gas formation exists with the folllowing substances:

Violent reactions possible with:

Water, Alkali metals, alkali compounds, Ammonia, Aldehydes, acetonitrile, Alkaline earth metals, alkalines, Acids, alkaline earth compounds, Metals, metal alloys, Oxides of phosphorus, phosphorus, hydrides, halogen-halogen compounds, oxyhalogenic compounds, permanganates, nitrates, carbides, combustible substances, organic solvent, acetylidene, Nitriles, organic nitro compounds, anilines, Peroxides, picrates, nitrides, lithium silicide, iron(III) compounds, bromates, chlorates, Amines, perchlorates, hydrogen peroxide

Conditions to avoid

no information available

Incompatible materials

animal/vegetable tissues, Metals
Contact with metals liberates hydrogen gas.
Metals

Hazardous decomposition products

in the event of fire: See section 5.
in the event of fire: See section 5.

SECTION 11. Toxicological information

Information on toxicological effects

Likely route of exposure
Eye contact, Skin contact

Target Organs
Eyes
Skin
Respiratory system
teeth
Mucous membranes

Skin irritation

Causes severe burns.

Eye irritation
Causes serious eye damage. Risk of blindness!

Teratogenicity
Did not show teratogenic effects in animal experiments. (IUCLID)

Specific target organ systemic toxicity - single exposure
The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific target organ systemic toxicity - repeated exposure
The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard
Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC	Group 1: Carcinogenic to humans	
	sulphuric acid	7664-93-9
OSHA	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
NTP	Known carcinogen.	
	sulphuric acid	7664-93-9
ACGIH	A2: Suspected human carcinogen	
	sulphuric acid	7664-93-9

Further information

After inhalation of aerosols: damage to the affected mucous membranes. After skin contact: severe burns with formation of scabs. After eye contact: burns, corneal lesions. After swallowing: severe pain (risk of perforation!), nausea, vomiting and diarrhea. After a latency period of several weeks possibly pyloric stenosis.
Handle in accordance with good industrial hygiene and safety practice.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Additional ecological information

Biological effects:
Forms corrosive mixtures with water even if diluted.
Harmful effect due to pH shift.
Endangers drinking-water supplies if allowed to enter soil or water.
Further information on ecology
Discharge into the environment must be avoided.

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14. Transport information

Land transport (DOT)

UN number	UN 1830
Proper shipping name	SULPHURIC ACID
Class	8
Packing group	II
Environmentally hazardous	--

Air transport (IATA)

UN number	UN 1830
Proper shipping name	SULPHURIC ACID
Class	8
Packing group	II
Environmentally hazardous	--
Special precautions for user	no

Sea transport (IMDG)

UN number	UN 1830
Proper shipping name	SULPHURIC ACID
Class	8
Packing group	II
Environmentally hazardous	--
Special precautions for user	yes
EmS	F-A S-B

SECTION 15. Regulatory information

United States of America

SARA 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Ingredients

sulphuric acid	7664-93-9	*96.5 %*

SARA 302

The following components are subject to reporting levels established by SARA Title III, Section 302:

Ingredients

sulphuric acid	7664-93-9

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Ingredients
sulphuric acid

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Ingredients
sulphuric acid

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

DEA List I
Not listed

DEA List II
Listed

Ingredients

sulphuric acid	7664-93-9

US State Regulations

Massachusetts Right To Know

Ingredients
sulphuric acid

Pennsylvania Right To Know

Ingredients
sulphuric acid

New Jersey Right To Know

Ingredients
sulphuric acid

California Prop 65 Components
WARNING: this product contains a chemical known in the State of California to cause cancer.

Ingredients
sulphuric acid

Notification status

TSCA:	All components of the product are listed in the TSCA-inventory.
DSL:	All components of this product are on the Canadian DSL

SECTION 16. Other information

Training advice
Provide adequate information, instruction and training for operators.

Labeling
Hazard pictograms

Signal Word
Danger

Hazard Statements
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary Statements
Prevention
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

Full text of H-Statements referred to under sections 2 and 3.

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Key or legend to abbreviations and acronyms used in the safety data sheet
Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date06/20/2017

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.