SIGMA-ALDRICH

Material Safety Data Sheet

Version 3.0
Revision Date 07/14/2007
Print Date 09/26/2008

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : **2-Butanone**

Product Number : 04380
Brand : Fluka

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052
Emergency Phone # : (314) 776-6555

2. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : MEK
Ethyl methyl ketone
Methyl ethyl ketone

Formula : C4H8O
Molecular Weight : 72.11 g/mol

CAS-No.	EC-No.	Index-No.	Concentration [%]
Ethyl methyl ketone			
78-93-3	201-159-0	606-002-00-3	-

3. HAZARDS IDENTIFICATION

Emergency Overview
OSHA Hazards
Flammable Liquid
Delayed target organ effects
Irritant
Target Organs
Central nervous system

HMIS Classification
Health Hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 0

NFPA Rating
Health Hazard: 2
Fire : 3

00000320

Reactivity Hazard 0

Potential Health Effects

Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Skin May be harmful if absorbed through skin. May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Eyes May cause eye irritation.
Ingestion May be harmful if swallowed.

4. FIRST AID MEASURES

General advice
Consult a physician. Show this safety data sheet to the doctor in attendance.Move out of dangerous area.

If inhaled
If breathed in, move person into fresh air. If not breathing give artificial respiration Consult a physician.

In case of skin contact
Wash off with soap and plenty of water. Consult a physician.

In case of eye contact
Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed
Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING MEASURES

Flammable properties
Flash point -3 °C (27 °F) - closed cup

Ignition temperature 516 °C (961 °F)

Suitable extinguishing media
For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Specific hazards
Flash back possible over considerable distance. Container explosion may occur under fire conditions.

Special protective equipment for fire-fighters
Wear self contained breathing apparatus for fire fighting if necessary.

Further information
Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions
Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions
Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods for cleaning up
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

RECEIVED
OCT 06 2008
Safety & Environmental Health

7. HANDLING AND STORAGE

Handling
Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Storage
Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place. Store under inert gas.

hygroscopic

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Ethyl methyl ketone	78-93-3	TWA	200 ppm 590 mg/m3	1994-09-01	US. American Conference of Governmental and Industrial Hygienists Threshold Limit Values for Chemical Substances in the Work Environment; Annual Reports for the Year 2004:Committees on Threshold Limit Values (TLVs) and Biological Exposure Indices (BEIs)
Remarks	Substances for which there is a Biological Exposure Index or Indices				
		STEL	300 ppm 885 mg/m3	1994-09-01	US. American Conference of Governmental and Industrial Hygienists Threshold Limit Values for Chemical Substances in the Work Environment; Annual Reports for the Year 2004:Committees on Threshold Limit Values (TLVs) and Biological Exposure Indices (BEIs)
	Substances for which there is a Biological Exposure Index or Indices				
		TWA	200 ppm 590 mg/m3	1989-03-01	US. Department of Labor - Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1000 Z-1-A
		STEL	300 ppm 885 mg/m3	1989-03-01	US. Department of Labor - Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1000 Z-1-A
		TWA	200 ppm 590 mg/m3	1993-06-30	US. Department of Labor - Occupational Safety and Health Administration (OSHA) Permissible

					Exposure Limits (PEL) 29 CFR 1910.1000 Air Contaminants.

Personal protective equipment

Respiratory protection
Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection
Handle with gloves.

Eye protection
Safety glasses

Skin and body protection
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures
Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	liquid, clear
Colour	colourless

Safety data

pH	no data available
Melting point	-87 °C (-125 °F)
Boiling point	79 - 80 °C (174 - 176 °F)
Flash point	-3 °C (27 °F) - closed cup
Ignition temperature	516 °C (961 °F)
Lower explosion limit	1.8 %(V)
Upper explosion limit	10.1 %(V)
Vapour pressure	95 hPa (71 mmHg) at 20 °C (68 °F)
Density	0.805 g/cm3
Water solubility	soluble
Partition coefficient: n-octanol/water	log Pow: 0.29
Vapour density	2.49 - (Air = 1.0)

10. STABILITY AND REACTIVITY

Storage stability
Stable under recommended storage conditions.

Conditions to avoid
Heat, flames and sparks.

Exposure to moisture.

Materials to avoid
Oxidizing agents, Strong reducing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions.
Carbon oxides

Hazardous reactions
Vapours may form explosive mixture with air.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

LD50 Oral - rat - 2,737 mg/kg

LC50 Inhalation - mouse - 4 h - 32,000 mg/m3

LC50 Inhalation - Mammal - 38,000 mg/m3

LD50 Dermal - rabbit - 6,480 mg/kg

Irritation and corrosion

Skin - rabbit - Skin irritation - 24 h

Sensitisation

no data available

Chronic exposure

no data available

Signs and Symptoms of Exposure

Central nervous system depression, Gastrointestinal disturbance, narcosis

Potential Health Effects

Inhalation	May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Skin	May be harmful if absorbed through skin. May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Eyes	May cause eye irritation.
Ingestion	May be harmful if swallowed.
Target Organs	Central nervous system.

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

no data available

Ecotoxicity effects

Toxicity to fish	mortality NOEC - Cyprinodon variegatus (sheepshead minnow) - 400 mg/l - 96 h
	LC50 - Pimephales promelas (fathead minnow) - 3,130 - 3,320 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates.	LC50 - Daphnia magna (Water flea) - > 520 mg/l - 48 h
	EC50 - Daphnia magna (Water flea) - 7,060 mg/l - 24 h

00000321

Further information on ecology

no data available

13. DISPOSAL CONSIDERATIONS

Product
Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging
Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)
UN-Number: 1193 Class: 3 Packing group: II
Proper shipping name: Ethyl methyl ketone

IMDG
UN-Number: 1193 Class: 3 Packing group: II EMS-No: F-E, S-D
Proper shipping name: ETHYL METHYL KETONE
Marine pollutant: No

IATA
UN-Number: 1193 Class: 3 Packing group: II
Proper shipping name: Ethyl methyl ketone

15. REGULATORY INFORMATION

OSHA Hazards
Flammable Liquid, Delayed target organ effects, Irritant

TSCA Status
On TSCA Inventory

DSL Status
All components of this product are on the Canadian DSL list.

SARA 302 Components
SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components
SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards
Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Ethyl methyl ketone	78-93-3	1989-12-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Ethyl methyl ketone	78-93-3	1989-12-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Ethyl methyl ketone	78-93-3	1989-12-01

California Prop. 65 Components
This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

RECEIVED
OCT 06 2008
Safety & Env.
Mgmt.

16. OTHER INFORMATION

Further information

Copyright 2007 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only., The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Co., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.