

SIGMA-ALDRICH

Material Safety Data Sheet

Version 3.4
Revision Date 01/09/2009
Print Date 11/25/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Ethanol
Product Number : 459836
Brand : Sigma-Aldrich
Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA
Telephone : +1 800-325-5832
Fax : +1 800-325-5052
Emergency Phone # : (314) 776-6555

2. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Ethyl alcohol
Formula : C₂H₆O
Molecular Weight : 46.07 g/mol

CAS-No.	EC-No.	Index-No.	Concentration
Ethanol			
64-17-5	200-578-6	603-002-00-5	-

3. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable Liquid, Target Organ Effect, Irritant

Target Organs

Nerves, Liver, Heart

HMIS Classification

Health Hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 0

NFPA Rating

Health Hazard: 2
Fire: 3
Reactivity Hazard: 0

Potential Health Effects

Sigma-Aldrich Corporation
www.sigma-aldrich.com

Page 1 of 7

Sigma-Aldrich - 459836
Delivery 0833995942-000010 Purchase Order 37305G

Inhalation
Skin
Eyes
Ingestion

May be harmful if inhaled. Causes respiratory tract irritation.
May be harmful if absorbed through skin. Causes skin irritation.
Causes eye irritation.
May be harmful if swallowed.

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING MEASURES

Flammable properties

Flash point 14.0 °C (57.2 °F) - closed cup

Ignition temperature 363 °C (685 °F)

Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Handling

Avoid inhalation of vapour or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Sigma-Aldrich - 459836
Delivery 0833995942-000010 Purchase Order 37305G

Sigma-Aldrich Corporation
www.sigma-aldrich.com

Page 2 of 7

Storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

hygroscopic

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Update	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m ³	1996-05-18	US. American Conference of Governmental and Industrial Hygienists Threshold Limit Values for Chemical Substances in the Work Environment; Annual Reports for the Year 2004; Committees on Threshold Limit Values (TLVs) and Biological Exposure Indices (BEIs)
Remarks	The agent (mixture, or exposure circumstance) is not classifiable as to its carcinogenicity to humans. Refers to Appendix A -- Carcinogens. 1996 Adoption				
		TWA	1,000 ppm 1,900 mg/m ³	1989-03-01	US. Department of Labor - Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1000 Z-1-A
		TWA	1,000 ppm 1,900 mg/m ³	1993-06-30	US. Department of Labor - Occupational Safety and Health Administration (OSHA) Permissible Exposure Limits (PEL) 29 CFR 1910.1000 Air Contaminants.

Personal protective equipment**Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves.

Eye protection

Safety glasses

Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Form liquid, clear

Colour colourless

Safety data

pH no data available

Melting point -114 °C (-173 °F)
114 °C (237 °F)

Boiling point 78 °C (172 °F)

Flash point 14.0 °C (57.2 °F) - closed cup

Ignition temperature 363 °C (685 °F)

Lower explosion limit 3.3 %(V)

Upper explosion limit 19 %(V)

Vapour pressure 59.5 hPa (44.6 mmHg) at 20.0 °C (68.0 °F)

Density 0.789 g/mL at 25 °C (77 °F)
0.789 g/mL at 20 °C (68 °F)

Water solubility completely soluble

10. STABILITY AND REACTIVITY**Storage stability**

Stable under recommended storage conditions.

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Alkali metals, Ammonia, Oxidizing agents, Peroxides

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - None known.

Hazardous reactions

Vapours may form explosive mixture with air.

11. TOXICOLOGICAL INFORMATION**Acute toxicity**

LD50 Oral - rat - 7,060 mg/kg

Remarks: Lungs, Thorax, or Respiration: Other changes.

LC50 Inhalation - rat - 10 h - 20000 ppm

Irritation and corrosion

Skin - rabbit - Skin irritation - 24 h
Eyes - rabbit - Mild eye irritation - 24 h

Sensitisation

no data available

Chronic exposure

Carcinogenicity - mouse - Oral

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease.

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity - Human - female - Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on Newborn: Drug dependence.

Signs and Symptoms of Exposure

Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Potential Health Effects

Inhalation	May be harmful if inhaled. Causes respiratory tract irritation.
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.
Ingestion	May be harmful if swallowed.
Target Organs	Nerves., Liver, Heart,

Additional Information

RTECS: KQ6300000

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

no data available

Ecotoxicity effects

Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 13,000.00 mg/l - 96 h
	LC50 - Oncorhynchus mykiss (rainbow trout) - 10,400.00 mg/l - 96 h
	LC50 - Pimephales promelas (fathead minnow) - 15,300.00 mg/l - 96 h
	LC50 - other fish - 10,000.00 mg/l - 24 h

Toxicity to daphnia and other aquatic invertebrates.	EC50 - Daphnia magna (Water flea) - 9.30 mg/l - 48 h
--	--

Further information on ecology

no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN-Number: 1170 Class: 3	Packing group: II
Proper shipping name: Ethanol	
Marine pollutant: No	
Poison Inhalation Hazard: No	

IMDG

UN-Number: 1170 Class: 3	Packing group: II	EMS-No: F-E, S-D
Proper shipping name: ETHANOL		
Marine pollutant: No		

IATA

UN-Number: 1170 Class: 3	Packing group: II
Proper shipping name: Ethanol	

15. REGULATORY INFORMATION

OSHA Hazards

Flammable Liquid, Target Organ Effect, Irritant

DSL Status

All components of this product are on the Canadian DSL list.

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Ethanol	CAS-No. 64-17-5	Revision Date 1989-12-01
---------	--------------------	-----------------------------

Pennsylvania Right To Know Components

Ethanol	CAS-No. 64-17-5	Revision Date 1989-12-01
---------	--------------------	-----------------------------

New Jersey Right To Know Components

Ethanol	CAS-No. 64-17-5	Revision Date 1989-12-01
---------	--------------------	-----------------------------

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, blrth, or any other reproductive defects.

16. OTHER INFORMATION**Further Information**

Copyright 2009 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.
The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Co., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.



SIGMA-ALDRICH

3050 Spruce Street
Saint Louis, MO, 63103 USA
Telephone: 877-744-1126
Fax: 800-325-5052
www.sigmaaldrich.com

00000113

11/25/2009

UNIV OF NORTH DAKOTA
SAFETY & ENVIRONMENTAL HEALTH
3851 CAMPUS RD STOP 9031
GRAND FORKS ND 58202
USA

Attached please find the Material Safety Data Sheets required for your recent order(s). Please note that we deliver MSDS documents to you for hazardous materials that you have not ordered previously, or if we have made significant changes to the MSDS content since your last order. In addition, you can access our complete MSDS library at www.sigmaaldrich.com. You may contact the MSDS department at 877-744-1126 or via email at msdsrequest@sial.com if you have any questions or comments.

Beginning in October 2006, we will be upgrading our computer system that produces MSDS documents. In addition to improving the overall look of our MSDS, the documents from our new system will feature improved data quality and increased regulatory data. We will be migrating our data to the new system for several months, and you will receive separate MSDS mailings from each system during this transition period. We will be sending you MSDS documents from the new system as you order those products, so that you may update your records accordingly. Please feel free to contact us with any questions or comments you may have during our transition.

Regulatory Information:

These MSDS documents are written in accordance with US OSHA Hazard Communication Standard 29 CFR 1910.1200.

Certain mixtures or trade name products that are supplied by Sigma-Aldrich, Inc., contain a toxic chemical or chemicals subject to the notification requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. This law requires certain manufacturers to report on annual emissions of specified toxic chemicals and chemical categories. Please refer to Section 15 of the MSDS document to determine if a Sigma-Aldrich product contains any SARA listed materials.

If you are unsure if you are subject to the reporting requirements of Section 313, or need more information, please call the EPA Emergency Planning and Community Right-To-Know Information Hotline: (800) 424-9346 or (703) 412-9810. Please note that if you repackage, or otherwise redistribute, these products to industrial customers, a notice similar to this one should be sent to those customers. Additionally, this information must be permanently affixed to, and included with, all Material Safety Data Sheets that are copied and distributed for these substances.

Delivery #'s: 0833995942, 0834000382, 0834000388

PO#: 37305G

459836 ETHANOL, 200 PROOF, ANHYDROUS, > = 99.5%

PO#: 37975H

438081 PHOSPHORIC ACID, > = 85 WT. % SOLN IN WAT&
E27408 1,2-DIMETHOXYETHANE, REAGENTPLUS, > = 99%

RECEIVED
NOV 25 2009
SAFETY & ENVIRONMENTAL
HEALTH

