



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### SECTION: 1. Product and company identification

#### 1.1. Product identifier

|                               |                                                                                                      |
|-------------------------------|------------------------------------------------------------------------------------------------------|
| Product form                  | : Substance                                                                                          |
| Trade name                    | : Oxygen, MediPure Oxygen                                                                            |
| CAS-No.                       | : 7782-44-7                                                                                          |
| Formula                       | : O <sub>2</sub>                                                                                     |
| Other means of identification | : Oxygen, Compressed; MediPure Oxygen; Aviator's Breathing Oxygen; USP Oxygen; Oxygen - Diving Grade |

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

|                              |                                                                                |
|------------------------------|--------------------------------------------------------------------------------|
| Use of the substance/mixture | : Medical applications.<br>Industrial use<br>Diving Gas (Underwater Breathing) |
|------------------------------|--------------------------------------------------------------------------------|

#### 1.3. Details of the supplier of the safety data sheet

Linde Inc.  
10 Riverview Drive  
Danbury, CT 06810-6268, USA  
www.lindeus.com

Linde Inc. 1-844-44LINDE (1-844-445-4633)

#### 1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24 hr/day 7 days/week  
— Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887  
(collect calls accepted, Contract 17729)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture


##### GHS-US classification

Ox. Gas 1 H270  
Press. Gas (Comp.) H280

#### 2.2. Label elements

##### GHS US labelling

Hazard pictograms (GHS US)



GHS03

GHS04

Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H270 - MAY CAUSE OR INTENSIFY FIRE; OXIDIZER  
H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

Precautionary statements (GHS US)

: P202 - Do not handle until all safety precautions have been read and understood.  
P220 - Keep/Store away from combustible materials, clothing.  
P244 - Keep reduction valves/valves and fittings free from oil and grease.  
P271+P403 - Use and store only outdoors or in a well-ventilated place.  
P370+P376 - IN CASE OF FIRE: Stop leak if safe to do so  
CGA-PG05 - Use a back flow preventive device in the piping.  
CGA-PG20+CGA-PG10 - Use only with equipment of compatible materials of construction and rated for cylinder pressure.  
CGA-PG22 - Use only with equipment cleaned for oxygen service.  
CGA-PG12 - Do not open valve until connected to equipment prepared for use.  
CGA-PG21 - Open valve slowly.  
CGA-PG06 - Close valve after each use and when empty.



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

### 2.3. Other hazards

Other hazards which do not result in classification : Breathing 80 percent or more oxygen at atmospheric pressure for more than a few hours may cause nasal stuffiness, cough, sore throat, chest pain, and breathing difficulty. Breathing oxygen at higher pressure increases the likelihood of adverse effects within a shorter time period. Breathing pure oxygen under pressure may cause lung damage and central nervous system (CNS) effects, resulting in dizziness, poor coordination, tingling sensation, visual and hearing disturbances, muscular twitching, unconsciousness, and convulsions. Breathing oxygen under pressure may cause prolongation of adaptation to darkness and reduced peripheral vision.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Name : Oxygen, compressed  
CAS-No. : 7782-44-7

| Name   | Product identifier  | %          |
|--------|---------------------|------------|
| Oxygen | (CAS-No.) 7782-44-7 | 99.5 – 100 |

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Move to fresh air. Get medical advice/attention.  
First-aid measures after skin contact : Adverse effects not expected from this product.  
First-aid measures after eye contact : Adverse effects not expected from this product. In case of eye irritation: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Consult an ophthalmologist if irritation persists.  
First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Vigorously accelerates combustion. Use media appropriate for surrounding fire. Water (e.g. safety shower) is the preferred extinguishing media for clothing fires. Use extinguishing media appropriate for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Oxidizing agent; vigorously accelerates combustion. Contact with flammable materials may cause fire or explosion.  
Explosion hazard : Prolonged exposure to fire may cause containers to rupture/explode.  
Reactivity : The product is non-reactive under normal conditions of use, storage and transport.



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### 5.3. Advice for firefighters

|                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Firefighting instructions                      | <p>: High-pressure, oxidizing gas.</p> <p>Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.</p> |
| Special protective equipment for fire fighters | <p>: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Specific methods                               | <p>: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</p> <p>Stop flow of product if safe to do so.</p> <p>Use water spray or fog to knock down fire fumes if possible.</p>                                                                                                            |
| Other information                              | <p>: Heat of fire can build pressure in container and cause it to rupture. Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by TC.) No part of the container should be subjected to a temperature higher than 125°F (52°C). Smoking, flames, and electric sparks in the presence of enriched oxygen atmospheres are potential explosion hazards.</p> <p>Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by TC.).</p>                            |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General measures                   | <p>: Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ensure adequate air ventilation. Eliminate ignition sources. Evacuate area. Monitor concentration of released product. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so. Ventilate area. Cool containers / tanks with spray water if possible. Stop leak if safe to do so.</p> |
| 6.1.1. For non-emergency personnel | No additional information available                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 6.1.2. For emergency responders    | No additional information available                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### 6.2. Environmental precautions

Try to stop release if safe to do so. Try to stop release. Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with container supplier/owner instructions.

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

See also sections 8 and 13.



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect containers from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

##### Safe use of the product

: **The suitability of this product as a component in underwater breathing gas mixtures** is to be determined by or under the supervision of personnel experienced in the use of underwater breathing gas mixtures and familiar with the physiological effects, methods employed, frequency and duration of use, hazards, side effects, and precautions to be taken.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Storage conditions

: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g. NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

**OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:** When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

#### 7.3. Specific end use(s)

None.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Oxygen, compressed (7782-44-7) |                 |
|--------------------------------|-----------------|
| ACGIH                          | Not established |
| USA OSHA                       | Not established |
| Oxygen (7782-44-7)             |                 |
| ACGIH                          | Not established |
| USA OSHA                       | Not established |

#### 8.2. Exposure controls

##### Appropriate engineering controls

: Avoid oxygen rich (>23,5%) atmospheres. Use a local exhaust system with sufficient flow velocity to maintain an adequate supply of air in the worker's breathing zone. Mechanical (general): General exhaust ventilation may be acceptable if it can maintain an adequate supply of air.

##### Hand protection

: Wear work gloves when handling containers; welding gloves for welding. Gloves must be free of oil and grease. Select hand protection in accordance with OSHA 29 CFR 1910.138.

##### Eye protection

: Wear safety glasses with side shields. Select eye protection in accordance with OSHA 29 CFR 1910.133.



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Skin and body protection | : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. As needed for welding, wear hand, head, and body protection to help prevent injury from radiation and sparks. (See ANSI Z49.1.) At a minimum, this includes welder's gloves and protective goggles, and may include arm protectors, aprons, hats, and shoulder protection as well as substantial clothing. Wear work gloves and metatarsal shoes for cylinder handling. Protective equipment where needed. Select in accordance with OSHA 29 CFR 1910.132, 1910.136, and 1910.138. |
| Respiratory protection   | : When workplace conditions warrant respirator use, follow a respiratory protection program that meets or exceeds the requirements of the appropriate Health and Safety Regulations. Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).                                                                                                                   |
| Other information        | : Consider the use of flame resistant safety clothing.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                                 |                                                                                                      |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------|
| Physical state                                  | : Gas                                                                                                |
| Appearance                                      | : Colourless gas.                                                                                    |
| Molecular mass                                  | : 32 g/mol                                                                                           |
| Colour                                          | : Colourless.                                                                                        |
| Odour                                           | : No odour warning properties.                                                                       |
| Odour threshold                                 | : No data available                                                                                  |
| pH                                              | : Not applicable.                                                                                    |
| Relative evaporation rate (butylacetate=1)      | : No data available                                                                                  |
| Relative evaporation rate (ether=1)             | : Not applicable.                                                                                    |
| Melting point                                   | : -219 °C (-362°F)                                                                                   |
| Freezing point                                  | : No data available                                                                                  |
| Boiling point                                   | : -183 °C (-297°F)                                                                                   |
| Flash point                                     | : Not applicable.                                                                                    |
| Critical temperature                            | : -118.6 °C (-181.48°F)                                                                              |
| Auto-ignition temperature                       | : Non flammable.                                                                                     |
| Decomposition temperature                       | : No data available                                                                                  |
| Flammability (solid, gas)                       | : No data available                                                                                  |
| Vapour pressure                                 | : Not applicable.                                                                                    |
| Critical pressure                               | : 50.4 bar (731.4 psia)                                                                              |
| Relative vapour density at 20°C                 | : 0.0827 lb/ft <sup>3</sup> (1.325 kg/m <sup>3</sup> ) absolute vapour density at 70°F/21.1°C, 1 atm |
| Relative density                                | : 1.1                                                                                                |
| Density                                         | : 1.4289 kg/m <sup>3</sup> (at 21.1 °C)                                                              |
| Relative gas density                            | : 1.1                                                                                                |
| Solubility                                      | : Water: 39 mg/l                                                                                     |
| Partition coefficient n-octanol/water (Log Pow) | : Not applicable.                                                                                    |
| Partition coefficient n-octanol/water (Log Kow) | : Not applicable.                                                                                    |
| Viscosity, kinematic                            | : Not applicable.                                                                                    |
| Viscosity, dynamic                              | : Not applicable.                                                                                    |
| Explosive properties                            | : Not applicable.                                                                                    |
| Oxidizing properties                            | : Oxidizer.                                                                                          |
| Explosive limits                                | : No data available                                                                                  |

### 9.2. Other information

|                        |                                                                                                          |
|------------------------|----------------------------------------------------------------------------------------------------------|
| Gas group              | : Compressed gas                                                                                         |
| Additional information | : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level. |



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Violently oxidizes organic material.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion. May react violently with combustible materials. May react violently with reducing agents.

#### 10.6. Hazardous decomposition products

None.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Not classified  
pH: Not applicable.  
Serious eye damage/irritation : Not classified  
pH: Not applicable.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : No ecological damage caused by this product.

#### 12.2. Persistence and degradability

##### Oxygen, compressed (7782-44-7)

|                               |                                              |
|-------------------------------|----------------------------------------------|
| Persistence and degradability | No ecological damage caused by this product. |
|-------------------------------|----------------------------------------------|

##### Oxygen (7782-44-7)

|                               |                    |
|-------------------------------|--------------------|
| Persistence and degradability | No data available. |
|-------------------------------|--------------------|



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### 12.3. Bioaccumulative potential

| Oxygen, compressed (7782-44-7)                  |                                              |
|-------------------------------------------------|----------------------------------------------|
| Partition coefficient n-octanol/water (Log Pow) | Not applicable.                              |
| Partition coefficient n-octanol/water (Log Kow) | Not applicable.                              |
| Bioaccumulative potential                       | No ecological damage caused by this product. |
| Oxygen (7782-44-7)                              |                                              |
| Partition coefficient n-octanol/water (Log Pow) | Not applicable.                              |
| Partition coefficient n-octanol/water (Log Kow) | Not applicable.                              |
| Bioaccumulative potential                       | No ecological damage caused by this product. |

### 12.4. Mobility in soil

| Oxygen, compressed (7782-44-7) |                                                                                                                              |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Mobility in soil               | No data available.                                                                                                           |
| Ecology - soil                 | No ecological damage caused by this product.                                                                                 |
| Oxygen (7782-44-7)             |                                                                                                                              |
| Mobility in soil               | No data available.                                                                                                           |
| Ecology - soil                 | Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely. |

### 12.5. Other adverse effects

|                           |                                       |
|---------------------------|---------------------------------------|
| Effect on the ozone layer | : None.                               |
| Effect on global warming  | : No known effects from this product. |

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

|                                            |                                                                                                                                                                                                                                              |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product/Packaging disposal recommendations | : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements. Dispose of contents/container in accordance with container supplier/owner instructions. |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## SECTION 14: Transport information

|                                      |                                             |
|--------------------------------------|---------------------------------------------|
| In accordance with DOT               |                                             |
| Transport document description (DOT) | : UN1072 Oxygen, compressed, 2.2            |
| UN-No.(DOT)                          | : UN1072                                    |
| Proper Shipping Name (DOT)           | : Oxygen, compressed                        |
| Transport hazard class(es) (DOT)     | : 2.2 (5.1)                                 |
| Hazard labels (DOT)                  | : 2.2 - Non-flammable gas<br>5.1 - Oxidizer |



|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOT Symbols                             | : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.                                                                                                                                                                                                                                                                                                                                                                                                    |
| DOT Special Provisions (49 CFR 172.102) | : 110 - Fire extinguishers transported under UN1044 may include installed actuating cartridges (cartridges, power device of Division 1.4C or 1.4S), without changing the classification of Division 2.2, provided the aggregate quantity of deflagrating (propellant) explosives does not exceed 3.2 grams per extinguishing unit.<br>A14 - This material is not authorized to be transported as a limited quantity or consumer commodity in accordance with 173.306 of this subchapter when transported aboard an aircraft. |

### Additional information

|                                       |                                           |
|---------------------------------------|-------------------------------------------|
| Emergency Response Guide (ERG) Number | : 122 (UN1072)                            |
| Other information                     | : No supplementary information available. |



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:  
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

### Transport by sea

UN-No. (IMDG) : 1072  
Proper Shipping Name (IMDG) : OXYGEN, COMPRESSED  
Transport hazard class(es) (IMDG) : 2.2 (5.1)  
Division (IMDG) : 2.2 - Non-flammable, non-toxic gases  
MFAG-No : 122

### Other information

: No supplementary information available.

### Air transport

UN-No. (IATA) : 1072  
Proper Shipping Name (IATA) : Oxygen, compressed  
Transport hazard class(es) (IATA) : 2.2 (5.1)  
Civil Aeronautics Law : Gases under pressure/Gases nonflammable nontoxic under pressure(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Oxygen, compressed (7782-44-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

### 15.2. International regulations

#### CANADA

#### Oxygen, compressed (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

#### Oxygen, compressed (7782-44-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### 15.2.2. National regulations

#### Oxygen, compressed (7782-44-7)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### 15.3. US State regulations

#### Oxygen, compressed(7782-44-7)

|                                                                     |                                                                                                                                                           |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List               | No                                                                                                                                                        |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No                                                                                                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No                                                                                                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male   | No                                                                                                                                                        |
| State or local regulations                                          | U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

#### Oxygen (7782-44-7)

|                                                       |                                                             |                                                                     |                                                                   |                                  |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No                                                    | No                                                          | No                                                                  | No                                                                |                                  |

#### Oxygen (7782-44-7)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List



# Oxygen, compressed

## Safety Data Sheet P-4638

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 06/20/2024 Supersedes: 02/03/2022 SDS US Version: 2.3

### SECTION 16: Other information

#### Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product.

Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from [www.lindeus.com](http://www.lindeus.com).

Linde and the Linde wordmark are trademarks or registered trademarks of Linde Inc. or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

#### Revision date

: 06/20/2024

#### NFPA health hazard

: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

#### NFPA fire hazard


: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

#### NFPA instability

: 0 - Material that in themselves are normally stable, even under fire conditions.

#### NFPA specific hazard

: OX - Materials that possess oxidizing properties.



SDS US (GHS HazCom 2012) - Linde 2022

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*