

Material Safety Data Sheet

Version 4.1
Revision Date 02/14/2011
Print Date 12/13/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Isobutyl acetate

Product Number : W217506
Brand : Aldrich
Product Use : For laboratory research purposes.

Supplier : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA
Telephone : +1 800-325-5832
Fax : +1 800-325-5052
Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555
Preparation Information : Sigma-Aldrich Corporation
Product Safety - Americas Region
1-800-521-8956

Manufacturer : Sigma-Aldrich Corporation
3050 Spruce St.
St. Louis, Missouri 63103
USA

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable liquid

GHS Classification

Flammable liquids (Category 2)

GHS Label elements, including precautionary statements

Pictogram



Signal word : Danger

Hazard statement(s)

H225 : Highly flammable liquid and vapour.

Precautionary statement(s)

P210 : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

HMIS Classification

Health hazard: 0

Flammability: 3

Physical hazards: 0

NFPA Rating

Health hazard: 0

Fire: 3

Reactivity Hazard: 0

Potential Health Effects

Inhalation : May be harmful if inhaled. May cause respiratory tract irritation.
Skin : May be harmful if absorbed through skin. May cause skin irritation.
Eyes : May cause eye irritation.

Ingestion

May be harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : $C_6H_{12}O_2$
Molecular Weight : 116.16 g/mol

CAS-No.	EC-No.	Index-No.	Concentration
Isobutyl acetate			
110-19-0	203-745-1	607-026-00-7	-

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid inhalation of vapour or mist.

RECEIVED
DEC 19 2011
Safety & Environ
Health

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Isobutyl acetate	110-19-0	TWA	150 ppm	USA, ACGIH Threshold Limit Values (TLV)
Remarks	Eye & Upper Respiratory Tract irritation			
		TWA	150 ppm 700 mg/m3	USA, OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	150 ppm 700 mg/m3	USA, Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in mg/m3 is approximate.			
		TWA	150 ppm 700 mg/m3	USA, NIOSH Recommended Exposure Limits

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Impervious clothing, Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form clear, liquid
Colour colourless

Safety data

pH no data available
Melting point/freezing point Melting point/Range: -99 °C (-146 °F) - lit.

Boiling point 115 - 117 °C (239 - 243 °F) - lit.
Flash point 22 °C (72 °F) - closed cup
Ignition temperature 423 °C (793 °F)
Autoignition temperature no data available
Lower explosion limit 1.3 %(V)
Upper explosion limit 10.5 %(V)
Vapour pressure 20 hPa (15 mmHg) at 20 °C (68 °F)
Density 0.867 g/cm3 at 25 °C (77 °F)
Water solubility no data available
Partition coefficient: n-octanol/water no data available
Relative vapour density 4.01
- (Air = 1.0)
Odour no data available
Odour Threshold no data available
Evaporation rate no data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Materials to avoid

Strong oxidizing agents, Strong bases

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides
Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - rat - 13,400 mg/kg

Inhalation LC50

no data available

Dermal LD50

LD50 Dermal - rabbit - > 17,400 mg/kg

Other information on acute toxicity

no data available

Skin corrosion/irritation

Skin - rabbit - Open irritation test

Serious eye damage/eye irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation	May be harmful if inhaled. May cause respiratory tract irritation.
Ingestion	May be harmful if swallowed.
Skin	May be harmful if absorbed through skin. May cause skin irritation.
Eyes	May cause eye irritation.

Signs and Symptoms of Exposure

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects

no data available

Additional Information

RTECS: AI4025000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish	LC50 - Leuciscus idus melanotus - 101 mg/l - 48 h
	LC0 - Leuciscus idus melanotus - 70 mg/l - 48 h
Toxicity to daphnia and other aquatic invertebrates.	LC50 - Daphnia magna (Water flea) - 250 mg/l - 24 h

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Aldrich - W217506
Delivery 0840486713-000010 Purchase Order 2705AR12107

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1213 Class: 3 Packing group: II
Proper shipping name: Isobutyl acetate
Reportable Quantity (RQ): 5000 lbs
Marine pollutant: No
Poison Inhalation Hazard: No

IMDG

UN number: 1213 Class: 3 Packing group: II EMS-No: F-E, S-D
Proper shipping name: ISOBUTYL ACETATE
Marine pollutant: No

IATA

UN number: 1213 Class: 3 Packing group: II
Proper shipping name: Isobutyl acetate

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard

Massachusetts Right To Know Components

Isobutyl acetate	CAS-No. 110-19-0	Revision Date 1993-04-24
------------------	---------------------	-----------------------------

Pennsylvania Right To Know Components

Isobutyl acetate	CAS-No. 110-19-0	Revision Date 1993-04-24
------------------	---------------------	-----------------------------

New Jersey Right To Know Components

Isobutyl acetate	CAS-No. 110-19-0	Revision Date 1993-04-24
------------------	---------------------	-----------------------------

RECEIVED
DEC 13 2011
Safety & Environmental
Health

Aldrich - W217506
Delivery 0840486713-000010 Purchase Order 2705AR12107

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Further Information

Copyright 2011 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.
The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Co., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.
