

## SAFETY DATA SHEET

Version 6.18  
Revision Date 09/08/2024  
Print Date 06/29/2026**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Toluene

Product Number : 179418  
Brand : SIGALD  
Index-No. : 601-021-00-3  
CAS-No. : 108-88-3

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765  
Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225  
Skin irritation (Category 2), H315  
Reproductive toxicity (Category 2), H361

SIGALD - 179418

Page 1 of 14

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336  
Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Central nervous system, H373

Aspiration hazard (Category 1), H304

Short-term (acute) aquatic hazard (Category 2), H401

Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H336

May cause drowsiness or dizziness.

H361

Suspected of damaging fertility or the unborn child.

H373

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

H401

Toxic to aquatic life.

H412

Harmful to aquatic life with long lasting effects.

Precautionary Statements

P201

Obtain special instructions before use.

P202

Do not handle until all safety precautions have been read and understood.

P210

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P260

Do not breathe mist or vapors.

P264

Wash skin thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

P273

Avoid release to the environment.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

P331

Do NOT induce vomiting.

P332 + P313

If skin irritation occurs: Get medical advice/ attention.

P362

Take off contaminated clothing and wash before reuse.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant

P403 + P233	foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep container tightly closed.
P405	Store in a well-ventilated place. Keep cool.
P501	Store locked up.
	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula	: C7H8
Molecular weight	: 92.14 g/mol
CAS-No.	: 108-88-3
EC-No.	: 203-625-9
Index-No.	: 601-021-00-3

Component	Classification	Concentration
<b>Toluene</b>		
	Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 3; H225, H315, H361, H336, H373, H304, H401, H412 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

**If swallowed**

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

**Unsuitable extinguishing media**

For this substance/mixture no limitations of extinguishing agents are given.

**5.2 Special hazards arising from the substance or mixture**

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

**5.3 Advice for firefighters**

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

**5.4 Further information**

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

**6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

**6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemisorb®). Dispose of properly. Clean up affected area.

## 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Toluene	108-88-3	TWA	100 ppm 375 mg/m <sup>3</sup>	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
		STEL	150 ppm 560 mg/m <sup>3</sup>	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
		TWA	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
	Remarks	Z37.12-1967		
		CEIL	300 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.12-1967		

		Peak	500 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.12-1967		
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Visual impairment Female reproductive Pregnancy loss 2023 Adoption Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen		
		TWA	100 ppm 375 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		ST	150 ppm 560 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits

### Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Toluene	108-88-3	Toluene	0.02 mg/l	In blood	ACGIH - Biological Exposure Indices (BEI)
	Remarks	Prior to last shift of workweek			
		Toluene	0.03 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)			
		o-Cresol	0.3mg/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)			

### Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute systemic effects	384 mg/m <sup>3</sup>
Workers	Inhalation	Acute local effects	384 mg/m <sup>3</sup>
Workers	Skin contact	Long-term systemic effects	384mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	192 mg/m <sup>3</sup>
Workers	Inhalation	Long-term local effects	192 mg/m <sup>3</sup>
Consumers	Inhalation	Acute systemic effects	226 mg/m <sup>3</sup>
Consumers	Inhalation	Acute local effects	226 mg/m <sup>3</sup>
Consumers	Skin contact	Long-term systemic effects	226mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	56.5 mg/m <sup>3</sup>
Consumers	Ingestion	Long-term systemic effects	8.13mg/kg BW/d

## Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	2.89 mg/kg
Sea water	0.68 mg/l
Fresh water	0.68 mg/l
Sea sediment	16.39 mg/kg
Fresh water sediment	16.39 mg/kg
Sewage treatment plant	13.61 mg/l
Aquatic intermittent release	0.68 mg/l

## 8.2 Exposure controls

### Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

#### Body Protection

Flame retardant antistatic protective clothing.

#### Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

### **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

---

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

a) Appearance	Form: liquid
b) Odor	benzene-like
c) Odor Threshold	0.2 ppm
d) pH	Not applicable
e) Melting point/freezing point	Melting point/ range: -93 °C (-135 °F)
f) Initial boiling point and boiling range	110 - 111 °C 230 - 232 °F
g) Flash point	4.4 °C (39.9 °F) - closed cup - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 7.1 %(V) Lower explosion limit: 1.2 %(V)
k) Vapor pressure	30.88 hPa at 21.1 °C (70.0 °F)
l) Vapor density	3.18
m) Density	0.865 g/mL at 25 °C (77 °F)
Relative density	No data available
n) Water solubility	0.58 g/l at 25 °C (77 °F) - partly soluble
o) Partition coefficient: n-octanol/water	log Pow: 2.73 at 20 °C (68 °F) - Bioaccumulation is not expected.
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	Not classified as explosive.
t) Oxidizing properties	none

### **9.2 Other safety information**

SIGALD - 179418

Page 8 of 14

Conductivity	< 0.01 $\mu\text{S}/\text{cm}$
Surface tension	27.73 mN/m at 0.516g/l at 25 °C (77 °F)
Relative vapor density	3.18

---

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

Vapors may form explosive mixture with air.

### **10.2 Chemical stability**

The product is chemically stable under standard ambient conditions (room temperature) .

### **10.3 Possibility of hazardous reactions**

Risk of explosion with:

fuming sulfuric acid

Nitric acid

silver

perchlorates

nitrogen dioxide

nonmetallic halides

halogen-halogen compounds

uranium hexafluoride

organic nitro compounds

Violent reactions possible with:

Strong acids

Strong oxidizing agents

sulfur

with

Heat.

### **10.4 Conditions to avoid**

Warming.

### **10.5 Incompatible materials**

No data available

### **10.6 Hazardous decomposition products**

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male - 5,580 mg/kg

(Directive 67/548/EEC, Annex V, B.1.)

LC50 Inhalation - Rat - male - 4 h - 25.7 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male - > 5,000 mg/kg

Remarks: (ECHA)

#### Skin corrosion/irritation

Skin - Rabbit

Result: irritating - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

#### Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

#### Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Ames test

Test system: *S. typhimurium*

Metabolic activation: with and without metabolic activation

Method: Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)

Result: negative

Test Type: Chromosome aberration test

Species: Rat

Cell type: Bone marrow

Application Route: Intraperitoneal

Result: negative

Remarks: (ECHA)

#### Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

Suspected of damaging the unborn child.

#### **Specific target organ toxicity - single exposure**

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### **Specific target organ toxicity - repeated exposure**

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### **Aspiration hazard**

Aspiration may cause pulmonary edema and pneumonitis.

### **11.2 Additional Information**

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 625 mg/kg - LOAEL (Lowest observed adverse effect level) - 1,250 mg/kg

RTECS: XS5250000

Drowsiness, irritant effects, Dizziness, Convulsions, Headache, Nausea, Vomiting, Circulatory collapse, somnolence, inebriation, Unconsciousness, respiratory arrest, CNS disorders, respiratory paralysis, death

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish	flow-through test LC50 - Oncorhynchus kisutch (coho salmon) - 5.5 mg/l - 96 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Ceriodaphnia dubia (water flea) - 3.78 mg/l - 48 h (US-EPA)
Toxicity to bacteria	static test EC50 - Bacteria - 84 mg/l - 24 h Remarks: (ECHA)
Toxicity to fish(Chronic toxicity)	flow-through test NOEC - Oncorhynchus kisutch (coho salmon) - 1.39 mg/l - 40 d Remarks: (ECHA)

Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity) NOEC - Ceriodaphnia dubia (water flea) - 0.74 mg/l - 7 d (US-EPA)

### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 20 d  
Result: 86 % - Readily biodegradable.  
Remarks: (IUCLID)

### 12.3 Bioaccumulative potential

Bioaccumulation Leuciscus idus (Golden orfe) - 3 d  
- 0.05 mg/l(Toluene)

Bioconcentration factor (BCF): 90

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

---

## SECTION 14: Transport information

### DOT (US)

UN number: 1294 Class: 3 Packing group: II  
Proper shipping name: Toluene  
Reportable Quantity (RQ): 1000 lbs  
Poison Inhalation Hazard: No

### IMDG

SIGALD - 179418

Page 12 of 14

UN number: 1294 Class: 3  
Proper shipping name: TOLUENE

Packing group: II

EMS-No: F-E, S-D

**IATA**

UN number: 1294 Class: 3  
Proper shipping name: Toluene

Packing group: II

---

**SECTION 15: Regulatory information**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	1000

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene	108-88-3	>= 90 - <= 100 %
---------	----------	------------------

**US State Regulations**

**Massachusetts Right To Know**

Toluene 108-88-3

**Pennsylvania Right To Know**

Toluene 108-88-3

**Maine Chemicals of High Concern**

Toluene 108-88-3

**Vermont Chemicals of High Concern**

Toluene 108-88-3

**Washington Chemicals of High Concern**

Toluene 108-88-3

**California Prop. 65**

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

---

**SECTION 16: Other information****Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 6.18

Revision Date: 09/08/2024

Print Date: 06/29/2026